

ROLINK

PCC900 300K USB PC Camera

USB Interface

Built-in Microphone

1/4" CMOS Sensor
Compatible With USB 1.1 & 2.0
USB Interface
MSN Messenger Supported
30fps Frame Rate
S/N Ratio of >48dB
Windows 98/98SE/2000/ME/XP Compatible



PCC900 300K USB PC CAMERA



Specifications

*Image Sensor: 1/4" CMOS Sensor *Picture Element: 640H x 480V Pixels *Picture Format: 160 x 120, 320 x 240, 640 x 480, CIF, QCIF *Data Format: RGB 24.1420

- *Interface: Compatible with USB 1.1 and 2.0
- *Frame Rate: 30fps
- *Minimum Illumination: 6 Lux
- *S/N Ratio: >48dB
- *Definition: >300 TV Line
- *Viewing Angle: 92 degrees horizontal
- *Camera Control: Saturation, Contrast, Sharpness
- *Aperture/Focal Range: F2.0/f3.60, 80mm to infinity
- *Storage/Operating Temperature: -10 ~ +70 degrees Celsius / 0 ~ +50 degrees Celsius
- *Bulti-In microphone
- *VP Eye software and MSN Messenger supported

Minimum Systems Requirements:

- *PC with Pentium MMX CPU 200MHz or above
- *An available USB 1.1 or 2.0 port
- *Operating System: Windows 98/98SE/2000/ME/XP
- *32MB of System RAM
- *12MB of free hard disk space
- *CD ROM Drive for installation drive

Singapore: FIDA INTERNATIONAL (S) PTE LTD Blk 105 Boon Keng Road #06-11/13 Singapore 339776

Tel: (65) 6392 5567 Fax: (65) 6392 5455 www.fida.com

Malavsia: FIDA SYSTEMS (M) SDN BHD

29 Jalan USJ 1/31,47600 Subang Java Selangor, Darul Ehsan Malaysia Tel: (603) 8024 9151 Fax: (603) 8024 9161 www.fida.com

*Specifications are subjected to change without prior notice

> Online Technical Support support@fida.com

Free Technical Support Hotline:

(65) 6296 5455 (SINGAPORE) (603) 8023 9151 (MALAYSIA0 9am - 5.45pm (MON-FRI) 9am - 1pm (SAT) Closed on Sundays & Public Holidays

http://www.fida.com PROLINK is manufactured under the authority of FIDA INTERNATIONAL (S) PTE LTD



Copyright 2005 PROLINK All Rights reserved. All brands or product names are trademark or registered trademarks of their respective owners.