

- Wide Viewing True Color Display High Resolution 1024 x 768
- Anti-Glare & Anti-Static Glass Surface Stylish Design 0.28mm Dot Pitch



PRO556D

15" CRT MONITOR

Features & Benefits

Full 15" viewable screen

Auto-Scale: Gives full screen display

Auto-Adjustment: Provides self-adjusting screen settings

True Color Support: Renders picture pure viewing

Specifications

CRT

-Type: 15" CRT

-Dot Pitch: 0.28mm

-Glass Surface: Anti-Glare, Anti Static

-Max Resolution: 1024 x 768

Input

-Video: RGB Analog (750hm,0.7 Vp-p) -Sync: H/V separated (TTL Pos/Neg) -Frequency: fh: 30-56KHz fv: 50-150Hz

Connector

-Signal: D-sub 15pin

Power

-Voltage: AC Input: 100-240V/50/60Hz

Controls

Power ON/OFF, Select, ADJ+, ADJ-, H-Size, V-Size, H-Phase, V-Center, Pincusion, Brightness, Contrast, Trapezium

*Specifications are subjected to change without prior notice

Video Input

-Bandwidth: 110MHz at -3dB (typ)

Regulations: FCC, CE

Environment

-Operating Temperature: 0 - +40 degress Celsius

-Humidity: 20% - 80%

-Storage Temperature: -20 to +60 degrees Celsius

-Humidity: 10% - 90%

Singapore:

FIDA INTERNATIONAL (S) PTE LTD

Blk 105 Boon Keng Road #06-11/13 Singapore 339776 Tel: (65) 6392 5567 Fax: (65) 6392 5455 www.fida.com

Malaysia:

FIDA SYSTEMS (M) SDN BHD

29 USJ 1/31,47600 Subang Jaya, Selangor Darul Ehsan, Malaysia Tel: (603) 8024 9151 Fax: (603) 8024 9161 www.fida.com

http://www.fida.com

PROLINK is manufactured under the authority of FIDA INTERNATIONAL (S) PTE LTD















Online Technical Support: support@fida.com

Free Technical Support Hotline:

(65) 6296 5455 (SINGAPORE) (603) 8023 9151 (MALAYSIA) 9am - 5.45pm (MON-FRI)

9am - 1pm (SAT)

Closed on Sundays & Public Holidays