

PROLINK®

Challenge The Limit

PRO998A

19" PURE FLAT CRT MONITOR

PROLINK PRO998A 19" Pure Flat CRT monitor provides a flicker free 1600 x 1200 resolution whereby you will enjoy plenty of desktop for easy viewing of spreadsheets, word processing or even the Internet! Its super fine dot pitch provides superior focus so that even the smallest type is easily readable. PRO998A delivers all the features you demand for consistent, quality and reliable performance!



Stylish Design



High Resolution



- Provides Full Screen Display • Self Adjusting Screen Settings • High Quality Image
- Wide Viewing • High Resolution 1600 x 1200dpi • Stylish Design
- Ultra Fine Dot Pitch of 0.25mm • Anti Glare & Anti Static Glass Surface
- True Color Support for Picture Pure Viewing • D-Sub 15 Pin Connector

PROLINK®

Challenge The Limit

PRO998A 19" PURE FLAT CRT MONITOR

Features

- Full 19" viewable screen
- VESA wall mounting - Allows easy mounting
- Auto-scale - Gives full screen display
- Auto-adjustment - Provides self-adjusting screen settings
- True colour support - Renders picture-pure viewing

Specifications

- **Picture Tube Diagonal:** 19 inches
- **Viewable Size:** 45.7cm (18)
- **Dot Pitch:** 0.25mm
- **Resolution (max):** 1600 x 1200
- **Recommend Model Resolution:**
1024 x 768 @ 85KHz
- **Use Control:** OSD CONTROL, Power ON/OFF
- **Control Function:** H-size, V-size, H-phase, V-center, Pincushion, Brightness, Contrast, Trapezium, Parallel, Balance, Rotation, Degauss, Colour, OSD Position, Zoom, H/V moire, Language, Recall, etc.

- **Scanning Frequency:** Hor.: 30 - 75KHz
Vert.: 50 - 150Hz
- **Video B/W:** 165MHz at -3dB
- **Power Input:** AC100 - 240V/50/60Hz
- **Power Consumption:** 100W max
- **Input Signal:** Video: Analog RGB 0.7pp/75ohm
Sync: Separate, Hor./Vert./ TTL
Pos./Neg.
Connector: D-sub 15-pin interface cable
- **Display Size:** 310mm x 225mm (adjustable)
- **Carton Dimension:** 576mm (L) x 526mm (W) x 510mm (H)
- **Packing Quantity:** 1*20 /160pcs, 1*40 ft/300pcs,
1*40 HQ/440pcs
- **Weight:** 19.5kg net / 22kg gross
- **Environment:**
Operation temp: 0-+40 degrees Celsius
Humidity: 20% - 80%
Storage temp: -20-+60 degrees Celsius
Humidity: 10% - 90%

**Specifications are subjected to change without prior notice*

Singapore

FIDA INTERNATIONAL (S) PTE LTD

Blk 105 Boon Keng Road #06-11/13

Kallang Basin Industrial Estate

Singapore 339776

Tel: (65) 6392 5567 Fax: (65) 6392 5455

Website: www.fida.com

Malaysia

FIDA SYSTEMS (M) SDN BHD

29 USJ 1/31

47600 Subang Jaya Selangor

Darul Ehsan Malaysia

Tel: (603) 8024 9151 Fax: (603) 8024 9161

Website: www.fida.com

<http://www.fida.com>

PROLINK is manufactured under the authority of **FIDA INTERNATIONAL (S) PTE LTD**



All brand or product names are trademark or registered trademarks of their respective owners

© Copyright 2004 PROLINK All Rights Reserved

Online Technical Support
support@fida.com

Free Lifetime Technical Support Hotline

9am - 5.45pm (MON-FRI)

9am - 1pm (SAT)

Closed on Sundays & Public Holidays

Tel: (65) 6296 5455 (SINGAPORE)

(603) 8024 9151 (MALAYSIA)