

**PROLiNK®**

Challenge The Limit

# PRO 190 Series

## 19" TFT LCD MONITOR

PROLiNK PRO 190 Series 19" TFT LCD Monitor is a high performance intelligent multi-scanning color monitor. It is with 19" TFT LCD screen and MCU digital control without radiation and glare. The monitor is slim, adapting to small places, saving you more space to your workstations.



Wall Mounted  
Enabled



Sleek &  
Slim



Built-In Speakers



- Plug & Play • Anti-Glare Surface Disposal • 250cd/m<sup>2</sup> Brightness
- High Resolution 1280 x 1024 • 16.7M Colors For High Quality Image
- Built-In Speakers • Windows 98/2000/NT/ME/XP Supported

# PROLINK®

Challenge The Limit



## PRO 190 Series 19" TFT LCD Monitor

### Features & Benefits:

Best Working Mode:	1280 x 1024 @ 60Hz
Viewable Angle:	H -80° / +80° V -80° / +80°
Active Area:	376.320mm x 301.056mm
Pixel Pitch:	0.294mm x 0.294mm
Brightness (Max):	250cd/m <sup>2</sup>
Contrast (Max):	600:1
Response Time:	2/10ms
Color:	16.7M colors
Auto Color Balance:	When connected to different graphic adapter, the monitor can calibrates the white and black reference voltage

Plug & Play  
Wall mounted enabled  
VESA Hanging Style Standard  
DVI Input Available (Applicable to PRO193A only)  
Built-In Speakers  
Power Saving Compliant  
VESA DPMS  
Compatible with Windows 98/2000/NT/XP/ME &  
VESA DDC 1/28

### Specifications:

Monitor Type:	TFT LCD
Surface Disposal:	Anti-Glare
Active Area:	376.320mm x 301.056mm
Input Resistance:	75 ± 3% Ω
H-Frequency:	30KHz - 80KHz
V-Frequency:	55KHz - 75Hz
Power Supply For Adapter:	100V - 240VAC 60Hz/50Hz
Power Supply For Monitor:	12VDC 4.2A
Rated Voltage/Consumption (Max):	12VDC 45W
Input Connector:	15 pins D-Sub
Operating Temperature:	5°C - 40°C
Humidity:	10% - 80%
Storage Temperature:	-20°C - 55°C

*\*Specifications are subjected to  
change without prior notice*

Singapore:

**FIDA INTERNATIONAL (S) PTE LTD**

Blok 105 Boon Keng Road

#06-11/13 Singapore 339776

Tel: (65) 6392 5567 Fax: (65) 6392 5455

[www.fida.com](http://www.fida.com)

<http://www.fida.com>

PROLINK is manufactured under the authority of FIDA INTERNATIONAL (S) PTE LTD

Malaysia:

**FIDA SYSTEMS (M) SDN BHD**

29 Jalan USJ 1/31, 47600 Subang Jaya,

Selangor Darul Ehsan, Malaysia

Tel: (603) 8024 9151 Fax: (603) 8024 9161

[www.fida.com](http://www.fida.com)

**Online Technical Support:**

[support@fida.com](mailto:support@fida.com)

**Technical Support Hotline:**

9am - 5.45pm (MON-FRI)

9am - 1pm (SAT)

Tel: (65) 6296 5455 (SINGAPORE)

Tel: (603) 8023 9151 (MALAYSIA)

Closed on Sundays & Public Holidays

