

# PROLINK®

Challenge The Limit

# PUN1200

## USB PRINT SERVER

PROLINK PUN1200 is a 2 USB and 1 parallel Internet Print Server which is USB 1.1 compliant and provides 2 USB 1.1 ports which supports 1.5Mbps (low speed) and 12Mbps (Full speed) data transmission rate. Each port will also automatically detects the make and model of the USB printer. In addition, PUN1200 also provides 1 DB-25 pin Centronics parallel port, supporting Bi-Directional communication. This USB print server is also compliant with IEEE 802.3/802.3u standard, 10/100Mbps, auto-sensing, auto MDIX (auto crossover), RJ-45 (UTP) connector.

### LED Indications



### 2 USB/1 Parallel Port



- 2 USB 1.1 Compliant Ports • DHCP (Client) Supported • Compliant with IEEE802.3/802.3u Standards
- Compliant with IEEE802.3/802.3u Standards • Auto-Sensing • Auto MDIX • RJ45 (UTP) Connector
- Windows-Based Setup Program • Web Interface Management • USB1.1 Standards Compliant
- Windows Print Monitor Technology Provided • Software Upgradeable
- Supports Windows 95/98/98SE/ME/NT 4.0/2000/XP/MAC OS8.1 or higher/UNIX/LINUX, Netware

# PROLINK®

Challenge The Limit

## PUN1200 1-PARALLEL + 2-USB PRINT SERVER

### Features

- **USB:** 2 USB 1.1-compliant ports. Each port supports 1.5Mbps (low speed) and 12Mbps (full speed) data transmission rate. Each port automatically detects the make and model of the USB printer.
- **Parallel:** 1 DB-25-pin Centronics port, supporting Bi-Directional communication
- **LAN:** Compliant with IEEE 802.3/803.2u standard, 10/100Mbps, auto-sensing, auto-MDI-X (auto cross-over), RJ-45 (UTP) connector

### Specifications

#### Key Software Specifications

- **Network Operating System Support :** Windows 95/98/98SE/Me, Windows NT 4.0/2000/XP, Mac OS 8.1 or higher, UNIX/Linux, NetWare (Bindery/NDS)
- **Network Protocol Support :** TCP/IP, IPX, NetBEUI, AppleTalk, LPR
- **Internet Printing Protocol (IPP) Support :** Yes
- **Windows Print Monitor Technology :** Yes
- **DHCP (client) Support :** Yes
- **Management :** Web Interface, Windows-based Setup Program, Telnet
- **Software Upgradeable :** Yes (supports TFTP & Web browser)
- **SNMP & HP Web JetAdmin Support :** Yes

#### Hardware Specifications

- **CPU :** High-performance 32-bit RISC micro processor
- **Flash :** 512Kbytes (extendable to 1Mbytes)
- **System Memory :** 2Mbytes (extendable to 4Mbytes)
- **USB :** USB 1.1 Standard Compliant Host Controller
- **LAN :** 10/100Mbps, Auto-sensing, Auto MDI-X (Auto cross-over)

\*Specifications are subjected to change without prior notice

Singapore

**FIDA INTERNATIONAL (S) PTE LTD**

Blk 105 Boon Keng Road #06-11/13

Kallang Basin Industrial Estate

Singapore 339776

Tel: (65) 6392 5567 Fax: (65) 6392 5455

Website: [www.fida.com](http://www.fida.com)

Malaysia

**FIDA SYSTEMS (M) SDN BHD**

29 USJ 1/31

47600 Subang Jaya Selangor

Darul Ehsan Malaysia

Tel: (603) 8024 9151 Fax: (603) 8024 9161

Website: [www.fida.com](http://www.fida.com)

<http://www.fida.com>

PROLINK is manufactured under the authority of **FIDA INTERNATIONAL (S) PTE LTD**



All brand or product names are trademark or registered trademarks of their respective owners

© Copyright 2004 PROLINK All Rights Reserved

**Online Technical Support**  
[support@fida.com](mailto:support@fida.com)

**Free Lifetime Technical Support Hotline**

9am - 5.45pm (MON-FRI)

9am - 1pm (SAT)

Closed on Sundays & Public Holidays

Tel: (65) 6296 5455 (SINGAPORE)

(603) 8024 9151 (MALAYSIA)