

# PROLINK®

Challenge The Limit

# PRO930 ONLINE UPS

Multiple Plug



Fax/Data Protection Sockets



- 32 Bits Data-Bus Microprocessor with Robust Processing Power
- RS232 Communication Port
- Automatic Disk Saving
- Automatic Time Switch ON/OFF
- Rated Load of 1KVA/800W
- Automatic Power Status Recordation
- Power Monitoring Software Provided



# PROLINK®

Challenge The Limit

## PRO930 ONLINE UPS

### Features

To meet the requirement of the network system to the power, Prolink has developed a new generation UPS--Pro on-line series. It adopts 32bits data-bus microprocessor with robust processing power that is capable of detecting and controlling quickly and accurately all movement of UPS to ensure product high reliability. Owe to the use of the double-conversion circuit design, the power used by load is the pure sine wave power by stabilizing voltage and stabilizing frequency and noisy signals filter. Furthermore, Pro On-line series UPS and the network server are connected together through the RS232 communication port and power monitoring software, which offers power status available at any time. Moreover, it achieves the intelligent functions such time self-inspection, automatic disk-saving, automatic time switch ON/OFF and automatic power status recordation, etc, so it achieves the zero distance of communication between user and UPS. When utility power is disconnected, UPS informs the server immediately and gets ready to be switched off and automatically saves all data before performing the normal switch-off instruction. Even in an unattended network environment, UPS can ensure data safety of the network system.

### Specifications

Ratings 3KVA (Online)

#### Input

Voltage range: 160-276Vac  
Frequency range: 46-54Hz  
Input PF: >0.95, conform to EN605552

#### Output

Voltage range: 220VAC  $\pm$  3%  
Frequency range:  $\pm$  0.5%  
Linear load Distortion: <3%  
Non linear load Distortion <56%  
Overload: >105 for 10s; >150% for 200ms  
Crest Factor: 3:1(max)

#### Battery

DC voltage: 96VDC  
Internal battery: 8x7AH

Charging time: 90%capacity after 8hrs charging  
Panel display: LED: Load, battery status, alarm

#### Interface Software

1. Power status
2. UPS shutdown
3. monitor UPS status
4. UPS self test
5. auto-save files

Noise Level <45dB  
Temperature: 0--40C  
Humidity: 0%-95%  
Operating altitude: <1500m  
Storage Temperature: -25 to 55 degree celcius  
Net/Gross Weight(Extension version): 19/21Kg  
Net/Gross Weight(Standard version): 34/36Kg  
Dimension(HxWxD): 330\*195\*455mm

Singapore

**FIDA INTERNATIONAL (S) PTE LTD**  
Blk 105 Boon Keng Road #06-11/13  
Kallang Basin Industrial Estate  
Singapore 339776  
Tel: (65) 6392 5567 Fax: (65) 6392 5455  
Website: www.fida.com

Malaysia

**FIDA SYSTEMS (M) SDN BHD**  
29 USJ 1/31  
47600 Subang Jaya Selangor  
Darul Ehsan Malaysia  
Tel: (603) 8024 9151 Fax: (603) 8024 9161  
Website: www.fida.com

*\*Specifications are subjected to change without prior notice*

<http://www.fida.com>

PROLINK is manufactured under the authority of **FIDA INTERNATIONAL (S) PTE LTD**



All brand or product names are trademark or registered trademarks of their respective owners  
© Copyright 2004 PROLINK All Rights Reserved

**Online Technical Support**  
[support@fida.com](mailto:support@fida.com)

**Free Lifetime Technical Support Hotline**

9am - 5.45pm (MON-FRI)  
9am - 1pm (SAT)  
Closed on Sundays & Public Holidays  
Tel: (65) 6296 5455 (SINGAPORE)  
(603) 8024 9151 (MALAYSIA)